

UTILITY
PATENT APPLICATION
TRANSMITTAL

Attorney Docket No.

P00,1790

First Named Inventor or Application Identifier

Paul Kunisch

Express Mail Label No: #EJ077704108US

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ Specification [Total Pages 12]
2. ☒ Drawing(s) (35USC 113) [Total Pages 1]
3. ☒ Declaration and Power of Attorney [Total Pages 2]
a. ☐ Executed declaration (Original Copy)
b. ☐ Copy from prior application (37CFR 1.63(d))
(for continuation/divisional with Box 14 completed)
i. ☐ [Note Box 4 Below]
DELETION OF INVENTOR(S)
Signed statement attached deleting
Inventor(s) named in the prior application,
see 37 CFR 1.63(d)(2) and 1.33(b).
4. Incorporation By Reference (usable if Box 3b is checked)
The entire disclosure of the prior application, from which a
copy of the oath or declaration is supplied under Box 3b,
is considered as being part of the disclosure of the
accompanying application and is hereby incorporated by
reference therein.

ACCOMPANYING APPLICATION PARTS

5. ☐ Assignment Papers (cover sheet & documentation)
6. ☒ Letter under 37 CFR 1.41(c).
7. ☐ English Translation Document (if applicable)
8. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
9. ☐ Preliminary Amendment
10. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
11. ☐ Small Entity Statement filed in prior application, Status still proper and desired
12. ☐ Certified Copy of Priority Document(s) German Application No. 199 46 442.1 filed September 28, 1999
13. ☐ Other:

14. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) ☐ of prior application No: /

CLAIMS AS FILED

(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) BASIC FEE \$690.00
TOTAL CLAIMS 20	6			
INDEPENDENT CLAIMS 3	1			
ANY MULTIPLE DEPENDENT CLAIMS? (YES (X) NO				
			TOTAL FILING FEE ->	\$690.00

☒ The Commissioner is hereby authorized to charge any additional fees which may be required in connection with this application, or credit any overpayment to ACCOUNT NO. 501-519. A duplicate copy of this sheet is enclosed.

☒ A check in the amount of \$ 690.00 to cover the filing fee is enclosed.

15. CORRESPONDENCE ADDRESS

Schiff Hardin & Waite
Patent Department
233 South Wacker Drive - 6600 Floor Sears Tower
Chicago, Illinois 60606
Telephone (312) 258-5500 - Fax (312) 258-5921

SIGNATURE:

Steven H. Noll #28,982

DATE: September 27, 2000

SCHIFF HARDIN & WAITE

A Partnership Including Professional Corporations

6600 Sears Tower, Chicago, Illinois 60606-6473
Telephone (312) 258-5500 Facsimile (312) 258-5700

Chicago
Washington
New York
Merrillville
Dublin

September 27, 2000

Assistant Commissioner for Patents,
Washington, D.C. 20231

RE: Proposed Patent Application for **PAUL KUNISCH** entitled:
Method for Recognizing an Off-Hook Condition
based on **one** German Patent Application: **19946442.1**
Filed: **September 28, 1999**
Attorney Docket No. **P00,1790**

Sir:

Under the provisions of 37 CFR §1.41 (c), I am filing the attached application with 6 Claims, 1 sheet of informal drawings, **un-executed Declaration**, and **filing fee** on behalf of **Paul Kunisch** and request that the application be assigned a serial number and filing date, pursuant to the provisions of 37 CFR §1.53 (b) and §1.53 (d).

Respectfully submitted,



Mark Bergner
Attorney for Applicant

(Reg. No. 45,877)

SPECIFICATION

TITLE

METHOD FOR RECOGNIZING AN OFF-HOOK CONDITION

BACKGROUND OF THE INVENTION

Field of the Invention

The invention is directed to a method for recognizing an off-hook condition of a terminal device at a two-wire subscriber line in a switching center or the like, in which the off-hook condition of a first terminal device working in a different frequency band at the same two-wire subscriber line is recognized by acquiring a loop d.c. current and the comparison thereof to a threshold (event threshold).

Description of the Related Art

It is necessary to reliably and unequivocally acquire the off-hook condition of subscriber-side terminal devices in a switching center at which the subscriber lines converge. For two-wire subscriber lines, a subscriber circuit is respectively allocated in the switching center that has an indicator allocated to it with which the off-hook condition of the subscriber-side terminal device is recognized.

This takes place by acquiring the loop current for analog terminal devices such as traditional telephone sets and fax devices. In the on-hook condition, i.e., when the handset is placed on the cradle switch, the terminating impedance of the terminal device is infinitely high (open loop), and thus no current flows via the two-wire line to the exchange circuit at which a voltage is applied.

As soon as the handset is taken from the cradle switch, the terminating impedance is comparatively low (approximately 300 Ω , which causes a loop d.c. current to flow via the two-wire line. This is recognized by an exchange circuit on the basis of an indicator. When this current exceeds a threshold, an off-hook condition is presumed, and all following circuits are activated, particularly the circuit arrangement that triggers the dial event and the connection event, etc.

The same procedure is also fundamentally possible when the subscriber-side terminal device is a digital terminal device that is connected to the two-wire subscriber line via a modem. It has become increasingly desirable to connect not only a single terminal device to a two-wire subscriber line but at least one further terminal device, the pair usually being an analog telephone and a digital terminal device. When the previously standard system of a two-party line is used, it is not possible to simultaneously operate of both terminal devices. However, it is desirable to also be able to transmit data in addition to a traditional telephone call, which is referred to as a "data-over-voice" application. Such applications are especially desirable in ADSL networks.

To achieve this, it was previously necessary to couple the digital terminal device via a POTS splitter and, further, to allocate a filter circuit capable of recognizing and coupling out the high-frequency part to the subscriber circuit at the exchange side. This made use of the fact that analog voice connections occur in a frequency range up to approximately 16 KHz, whereas digital data connections occur in a frequency range above 30 KHz.

Since the recognition of the off-hook condition must be dependable, it is necessary in this application to allocate not only an indicator to each subscriber circuit in the switching center but also a filter or, respectively, some other recognition circuit with respect to the transmission of

digital data.

These two recognition circuits, indicator and filter, must be constantly in operation and therefore require the constant supply of electrical power. Furthermore, the resulting heat produced requires additional measures such as aerators or similar mechanisms in order to eliminate this heat. The power consumption, which is referred to as consumed power, lies in the range of less than 1 W per subscriber, but must be expended for all subscribers. Since only some of the subscribers connected to the switching center are activated, i.e., are operated in the off-hook condition, a power consumption of some number of watts arises only for such off-hook subscribers.

The power required for a plurality of subscribers connected in the switching center is therefore not negligible. This is reflected in the capital and operating costs and, thus, in the connection charges that every subscriber must pay.

SUMMARY OF THE INVENTION

It is therefore an object of the invention to specify a method for recognizing the off-hook condition of further terminal devices at the same two-wire subscriber line of a first terminal device that allows a reduction in the consumable power that must be provided, in which a loop d.c. of a two-wire subscriber line with a first terminal device working in a first frequency band is acquired and compared to the acquired loop d.c. to a threshold, thus recognizing an off-hook condition of the first terminal device.

This object is inventively achieved in that the loop d.c. is compared to a second threshold that is higher than the first threshold by the current level minimally required given operation of the first terminal device. One of the terminal devices is an analog terminal device and the other

terminal device is a digital or data terminal device. One preferred embodiment sets the first threshold at approximately 10 mA. A d.c. resistance of the digital or data terminal device may be determined such that it corresponds to that of an analog terminal device at least at a beginning of an off-hook condition. This d.c. resistance may be preferably set at 300 Ω . The inventive method may further comprise the step of lowering the d.c. resistance of the digital or data terminal device after recognition of the off-hook condition at the digital or data terminal device and a beginning of a data transmission, to approximately 5 mA with an active current source.

The invention proceeds on the basis that the recognition of the off-hook condition of a digital terminal device is also fundamentally possible via the acquisition of the loop current and that, further, a quiescent condition occurs in which only a slight loop d.c. flows once an off-hook condition has been detected. When an off-hook condition has been acquired on the one hand and a further off-hook condition is acquired, it is possible on the basis of the following circuit arrangements in the exchange to determine the type of terminal equipment that caused the respective off-hook condition.

Accordingly, only a single indicator that constantly operates is required in the exchange for each two-wire subscriber line, i.e., for each subscriber circuit. The power consumption is thus low with the consumable power only amounting to a few mW. The additional requirement to provide consumable power for each type of terminal equipment is eliminated; on the contrary, only a specific consumable power need be made available per two-wire line regardless of the number of terminal devices connected at the subscriber side.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is explained in greater detail on the basis of the exemplary embodiments schematically shown in the Figure, which is a schematic diagram illustrating the inventive method.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

First, the Figure shows a subscriber 1 that is connected via a two-wire subscriber line 4 - shown as a stranded line - to an appertaining subscriber circuit 6 in a switching center/exchange 5 or the like. Both an analog terminal device 2 such as a telephone or telefax device as well as a digital terminal device 3 for data transmission, exemplified by a modem, are directly connected to the two-wire subscriber line 4 at the side of the subscriber 1. The subscriber circuit 6 exhibits a standard structure and, in particular, comprises an indicator 7 that is capable of detecting the amount of current i flowing over the two-wire subscriber line 4.

The subscriber 1 can be either the calling or the called subscriber. There are therefore two different line conditions:

- a) on the part of the calling subscriber:
 - a1) both the analog terminal device 2 as well as the digital terminal device 3 (modem) are in the quiescent condition (loop current $i = 0$);
 - a2) the analog terminal device 2 is picked up (off-hook) and a dialed connection is setup or, respectively, is placed down (on-hook), which releases the dialed connection, while the digital terminal device 3 is in the quiescent condition;
 - a3) the off-hook condition is triggered at the digital terminal device 3, for example by a pilot tone, a start protocol or by mechanical actuation of a switch or the like, as a result of

which a data connection is setup, where a data connection is also ended in the same way,
while the analog terminal device 2 remains in the quiescent condition;

a4) the connection (telephone connection) relating to the analog terminal device 2 remains
and the off-hook condition is additionally triggered at the digital terminal device 3 and
5 the data connection is setup or, respectively, such a data connection is in turn ended;

a5) for an existing data connection from the digital terminal device 3, the off-hook condition
is triggered at the analog terminal device 2 (for instance by lifting up the handset from the
cradle switch) and a dialed connection is set up or, respectively, is in turn released by
hanging up;

10 b) at the side of the called subscriber:

b1) both the analog terminal device 2 as well as the digital terminal device 3 (modem) are in
the quiescent condition (loop current $i = 0$);

b2) the analog terminal device 2 is called and the call is answered at this device (off-hook),
while the digital terminal device 3 continues to remain in the quiescent condition;

15 b3) the digital terminal device 3 (modem) is activated by a pilot tone (start protocol) while the
analog terminal device remains in the quiescent condition;

b4) for an existing data connection to the digital terminal device 3, the analog terminal device
2 is called and its off-hook condition is triggered by answering the call;

20 b5) for an existing voice connection (telephone connection) to the analog terminal device 2,
the digital terminal device 3 is activated by a pilot tone (start protocol).

Except for the line conditions a1 and b1 where no loop current flows ($i = 0$), the current
that can be acquired in terms of its amount by the indicator 7 flows for the other line conditions.

10070648-092700
154250" 8490290
The indicator 7 of the subscriber circuit 6 in the exchange is always operating in order to identify whether a DC current differing from zero flows over the two-wire subscriber line 4 and whether this exceeds a specific event threshold or a threshold. When this loop DC exceeds a threshold that currently lies at approximately 10 mA for recognition of the off-hook condition at analog
5 terminal devices 2, one (at least) of the two terminal devices is in the off-hook condition or activated, since a loop DC that can be acquired by the indicator 7, and exceeds the event threshold, flows.

This is also fundamentally possible given the digital terminal device 3. When the DC resistance of the modem of the digital terminal device 3 is brought at least initially to a value that corresponds to the DC resistance of the analog terminal device 2, currently approximately 300 Ω , then the off-hook condition that the digital terminal device 3 works in, operates in the same way via a loop DC i of the same order of magnitude. Following the setup of the data connection, it is expedient to reduce the loop DC flowing during the data connection, for instance by raising the DC resistance with the assistance of an active current source or sink 8 to approximately 5 mA. As a result of the change of the loop DC i when the handset of the analog terminal device 2 is picked up given an existing data connection, this new off-hook condition can be acquired as a result.

20 This is conversely possible given an existing analog telephone connection and subsequently triggered off-hook condition at the digital terminal device 3. When the further off-hook condition has been initially recognized in the exchange 5, all further circuit measures necessary at the exchange can be triggered for the setup of the connection, the transmission of dial tones, interpretation of dialed pulses, etc.

The same thing fundamentally occurs when the subscriber 1 is called at his analog terminal device 2, unless his digital terminal device 3 is activated.

In the simplest embodiment, it is not possible without further effort to call analog terminal devices to give an existing data connection between digital terminal devices 3, since a call disconnect already occurs given a few mA, and the threshold may not be arbitrarily raised. Moreover, the application of the call to the digital terminal device 3 at the low-impedance loop closure of approximately $300\ \Omega$ that has been set forth is also not possible independently of the problem triggered due to the call disconnect, since an impedance of at least $1400\ \Omega$ must be present during the call for performance reasons.

This problem can be overcome in that said active current limitation in the digital terminal device 3 is implemented with an active current sink at approximately 5 mA. As a result, a dependable call disconnect occurs due to high current change for an off-hook (answering) at the analog terminal device 2 in the call condition (a threshold of approximately 10 mA), where this current sink in the digital terminal device 3 represents an extremely high impedance for the ringing signal (to the analog terminal device 2), and as a result, the ringing signal to the analog terminal device 2 is not noticeably burdened.

The inventive procedure thus makes it possible to reliably recognize all line conditions, namely with a single indicator 7 for indicating the loop DC in the subscriber circuit 6 of the exchange 5 that has an essentially traditional structure and must at most be designed for recognizing two different thresholds. Thus, only a small amount of consumable power needs to be made available in the exchange 5 for all subscriber circuits.

The above-described method is illustrative of the principles of the present invention.

Numerous modifications and adaptations of it will be readily apparent to those skilled in this art without departing from the spirit and scope of the present invention.

004260" 8190/350

WHAT IS CLAIMED IS:

1. A method in a communications system having a first terminal device and a second terminal device, said method recognizing an off-hook condition of said second terminal device at a two-wire subscriber line in a switching center, comprising the steps of:

5 acquiring a loop d.c. of a two-wire subscriber line with a first terminal device working in a first frequency band and comparing said acquired loop d.c. to a threshold, thus recognizing an off-hook condition of said first terminal device; and

comparing said loop d.c. to a second threshold that is higher than said first threshold by a minimally required current level in operating said first terminal device.

10 2. A method according to claim 1, wherein one of said first terminal device and said second terminal device is an analog terminal device and the other terminal device is a digital or data terminal device.

15 3. A method according to claim 1, wherein said first threshold is approximately 10 mA.

20 4. A method according to claim 2, wherein a d.c. resistance of said digital or data terminal device is determined such that it corresponds to that of an analog terminal device at least at a beginning of an off-hook condition.

5. A method according to claim 4, wherein said d.c. resistance is 300 Ω .

6. A method according to claim 4, further comprising the step of:


lowering said d.c. resistance of said digital or data terminal device after recognition of

5 said off-hook condition at said digital or data terminal device and a beginning of a data transmission, to approximately 5 mA with an active current source.

002260"092700
05670643
05670643

ABSTRACT

The invention is directed to a method for recognizing, in a system having a first terminal device and a second terminal device connected to a two-wire subscriber line, an off-hook condition of the second terminal device (2; 3) at the two-wire subscriber line (4) in a switching center (5) or the like, in which the off-hook condition of a first terminal device (3; 2) working in a different frequency band than the second terminal device at the same two-wire subscriber line is recognized by acquiring a loop d.c. (i) and comparing it to a threshold. For reducing the consumable power to be made available in the switching center (5), the invention provides that the loop d.c. (i) is compared to a second threshold that is higher than the first threshold by the minimally required current level in the operation of the first terminal device (3; 2). All off-hook conditions can thus be dependably recognized in the fundamentally same way without providing additional devices and therefore having to make additional consumable power available.



DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD FOR RECOGNIZING THE OFF-HOOK CONDITION

Case No. P00,1790, the specification of which

(check one) ☒ is attached hereto.
☐ was filed on _____, as
Application Serial No. _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent Office all information which is known to me to be material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, 1.56.¹

I do not know and do not believe this invention was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, and I believe that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve months prior to this application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns, except as identified below:

I hereby claim foreign priority benefits under Title 35, United States Code, 119 of any foreign application(s) for patent or inventor's certificate listed below

Prior Foreign Application(s)

Number

Country

Date

19946442.1

Germany

September 28, 1999

and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the above listed application on which priority is claimed:

Prior Foreign Application(s)

Number

Country

Date

¹ (b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

(1) It establishes, by itself or in combination with other information, a *prima facie* case of unpatentability of a claim; or

(2) It refutes, or is inconsistent with, a position the applicant takes in:

(i) Opposing an argument of unpatentability relied on by the Office, or

(ii) Asserting an argument of patentability.

A *prima facie* case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

If no priority is claimed, I have identified all foreign patent applications filed prior to this application:

Prior Foreign Application(s)

Number

Country

Date

And I hereby appoint Messrs. John D. Simpson (Registration No. 19,842), Steven H. Noll (28,982), Brett A. Valiquet (27,841), James D. Hobart (24,149), Melvin A. Robinson (31,870), and Mark Bergner (45,877) all members of the firm of Schiff, Hardin & Waite, Patent Department,

Telephone: 312-258-5500

my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and direct that all correspondence be forwarded to:

Schiff, Hardin & Waite
Atten: Patent Department
6600 Sears Tower, Chicago, Illinois 60606 -6473

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor PAUL KUNISCH

Inventor's signature _____ Date _____

Residence Puchheim, Germany

Citizenship Germany

Post Office Address Rotwandstrasse 16

82178 Puchheim, Germany

Full name of second joint inventor,
(if any) _____

Inventor's signature _____ Date _____

Residence _____

Citizenship _____

Post Office Address _____

Full name of third joint inventor,
(if any) _____

Inventor's signature _____ Date _____

Residence _____

Citizenship _____

Post Office Address _____

00220-81902960